Approved For Release 2002/10/29: CIA-RDP63-00313A000600010062-7 Cy /of 27 June 1958 MEMORANDUM FOR: Special Assistant to the Director for Planning and Development SUBJECT : Camera Port Covers In response to your query of 20 June, the following information is submitted: a. The purpose of the camera port covers is to protect the surfaces of the glass: (1) while the aircraft is parked on the ramp (i. e., sand and gravel, debris, etc. blasted onto window surfaces by other aircraft, and (2) during take-off roll from debris deflected from wheels, splash of mud during inclement b. In actual practice, it has been determined that: 25X1A (1) Since remains in hangar until immediately prior to take-off on operational missions, damage to camera ports caused by run-up of other aircraft is not likely. (2) On aircraft with tricycle landing gear, debris, mud, etc. deflected onto the camera ports by the nosewheel during take-off can cause serious damage to camera port glasses and impair the quality of photography taken thru such glass. However, since the U-2 is tandem-wheeled and since the camera ports are fore of the main tandem wheel, damage from this source is not a problem. As you are aware, the system originally used was for the pilot to eject the camera hatches after take-off but prior to reaching the end of the runway. A vehicle would then be dispatched to the runway and hatches collected for reuse. Since it appeared that the hatches were not needed insofar as protecting the port glasses (see paragraph 1 b (1) and (2)) and since the hatches did not always eject properly, Detachment "B" commenced removing camera port hatches prior to take-off approximately one year ago. Until recent reports indicated the 2 left "B" camera port cover had failed to eject on two occasions, it was assumed that Detachment "C" was also manually removing ports prior to take-off. On receipt of this information, queried q 25X1A unit as to 25X1A 25X1A25X1A 4578 - IN 41449) indicated general agreement with removing ports prior to take-off and proposing that, if Project Headquarters 25X1A adopts this procedure, that the camera port cover ejection system be removed and that the weight gained be used for installation of an Omni-

directional navigational system.

- 2 -

2	5	X	1	Δ
_	u	$^{\sim}$	- 1	$\boldsymbol{\vdash}$

3. unit has been notified to remove camera port covers prior to take-off on photographic missions (copy of message attached).

4. An evaluation of the camera port ejection system versus an Omni-directional navigational system will be completed as soon as possible. At present, the camera port covers afford protection to the glass when aircraft are flown on transition or ferry flights with camera hatches installed. A preliminary opinion is that the port glasses could be covered with masking tape or that light weight manual ejection system could be devised to replace the existing system.

25X1A

Director of Operations

Attachment (1):
Cy msg.

DPS/DCI/RSQ:aem

Dist.:

0 - addressee

2 - Col Burke

5 - Chal file

6 - Ops subj

7 - Ops chron

25X1A

	UNCLASSIFIED	CONFIDENT		SECRET		
		L INTELLIGENCE AG		[
	OFFICIAL ROUTING SLIP					
	TO NAME AND	ADDRESS	INITIALS	DATE		
	1	Bn				
	2					
	3					
	4					
	5					
	6					
	ACTION	DIRECT REPLY DISPATCH FILE INFORMATION	PREPARE	REPLY		
	APPROVAL			IENDATION		
	COMMENT		RETURN			
	Remarks: Doris:					
X1A	action taken co	t we hand this prives. Please	tached. L paper to give me	M r B	25	
(1A						
	FOLD H	IERE TO RETURN TO	SENDER			
		HERE TO RETURN TO		DATE		